

Network-, Control-, & Dome-Keyboards



Features

- Support HDCVI/Analog/IP Video input
- Keyboard to Control
- -Dahua High Speed Dome (all models)
- -Dahua Standalone DVR (KBD1000 & NKB1000 only)
- -Dahua Network High Speed Dome (NKB1000 only)
- -Network Video Server (NKB1000 only)
- Connection
- -NKB1000: RS485, RS422, USB, RS232 & Network
- -KBD1000: RS485, RS422, USB & RS232
- -KB1000 : RS485, RS422 & USB
- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control
- Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips
- Connect to SmartPSS via USB (NKB1000 only)

Specifications

Model	NKB1000
General	
Keyboard Keypanel	Electromechanical
Joystick	3-axis, vector-solving, with twisting, return to-center head
Keyboard Communication	Direct Mode, Network Mode
Direct Mode	Interface: RS232/RS485 DVR Protocol: DH2 Dome Protocol: DH-SD/PELCO-D/PELCO-P/PELCO-D1/PELCO-P1.....
Display	LCD, 75.2mm x 33.85mm
Environmental	
Power Supply	Power adapter, input 100V~240V 50Hz / 60Hz,output DC12V/1000mA
Power Consumption	5W
Working Temperature	-10°C~+55°C
Working Humidity	10%~90%
Atmosphere Pressure	86kpa~106kpa
Dimension	330mmx160(140)mmx37.5(21)mm (WxD×H) (height: 100mm including joystick)
Weight	2.5 KG