

DH-NVS0104HE

1 Channel 960H Network Video Encoder



Features

- > Full channel@960H realtime encoding
- > Support TV output with simple OSD display
- > Support quota video, multi-channel video synchronous playback
- > Support Mark Playback
- > Support high quality two-way talk
- > 1 channel video and audio inputs

DH-NVS0104HE

Technical Specifications

Model	DH-NVS0104HE
System	
Main Processor	High performance dual-core embedded microprocessor
Operating System	Embedded LINUX
Recording	
Video Compression	H.264
Audio Compression	G.711A、G.711U、PCM
Video	
Video Input	1 channel(NTSC/PAL) BNC (1.0VP-P, 75Ω)
Video Output	1 channel PAL/NTSC, BNC (1.0VP-P, 75Ω)
Video Standards	PAL (625Line, 50f/s), NTSC (525Line, 60f/s)
Recording Speed	Realtime mode: PAL 1f/s-25f/s, NTSC 1f/s-30f/s
Display Split	1
Resolution	PAL (625Line, 50f/s), NTSC (525Line, 60f/s)
	Realtime surveillance 960H 960×576
	Main stream Resolution
	960H 960×576/ 960×480
	D1 704×576/ 704×480
	HD1 352×576/ 352×480
	2CIF 704×288/ 704×240
	CIF 352×288/ 352×240
	QCIF 176×144/176×120
	Support Dual Record Rate , Extra stream CIF 352×288/ 352×240 、QCIF 176×144/176×120
Image Quality	6-level adjustable
Privacy Masking	With an any size area for shelter protection in full screen, 4 rectangular zones (each camera)
Audio	
Audio Input	1 channel 200-2000mV 10KΩ (RCA) 1 channel input, 3.5mm JACK MIC IN
Audio Output	1 channel output, 3.5mm JACK LINE OUT
Two-way Talk	Multiplexing audio output
Storage	
Storage Mode	SD Network
Interface	
SD	1 Port
Alarm	4 channel input 2 channel output
Network	RJ-45 (10/100Base-T)
RS485	PTZ control, Support for multiple protocols

DH-NVS0104HE

Antenna Interface	Can be connected to a wireless antenna
General	
Power Supply	DC +12V / 3.3A
Power Consumption	<5W
Working Temperature	-10°C — +55°C
Working Humidity	10%—90%
ATM	86kpa~106kpa
Dimension	137mm×162mm×30mm
Weight	1.3KG
Installation	Desktop installation

System Connection

